

LIQUID XCD DATA SHEET

GENERAL INFORMATION

LIQUID XCD is liquid viscosifier slurry in texture. This is suspended in light naphthenic process oil. The Xanthan gum contained within is an American made material of highest quality standards.

APPLICATION

Very effective for all water based and completion fluid systems as spacer, sweeps, or displacement applications or additional rheology and hole cleaning where inadequate 3 and 6 rpm readings need correction.

PHYSICAL PROPERTY

- Specific Gravity at 70°F: 1.07
- Density (lbs per gallon): 8.8
- Flash Point: 270°F
- PH: Neutral
- Weight per Pail: 47 lbs gross
- Activity per Pail: 43%

ADVANTAGES

Will mix with minimum shear where dry Xanthan may clump. This material has a long shelf life, will not hard pack or settle in pail. No fish eyes. Will pour with ease directly out of pail; “zip lid” will open and close without use of knife or sharp object. Liquid XCD will typically require 1.5 to 2.0 lbs per barrel to perform most oilfield daily applications. Additional material may not raise “funnel viscosity” but raise 3-6 rpm instead.

SAFE HANDLING

Handle as an Industrial Chemical, wearing protective equipment and observing the precautions as described on the Safety Data Sheet (SDS).

PACKAGING

LIQUID XCD is packaged in 5 gallon pails or tote tanks at customer’s request.